

# DIBOND®

## DIBOND®structure

## STYLE TAKES CENTRE STAGE

With its black or optionally white surface, DIBOND®structure ensures bright accents. Especially as an eye catcher, used selectively to accentuate or extensively for full cladding, high quality products can be represented with DIBOND®structure in an excellent way. Applications cover the fields of shop fitting, wall cladding, interior design, bars and counters.

DIBOND®structure gets its characteristic look by using a special coating system that provides the panel with a haptic surface which is extremely durable.

With regard to processing, DIBOND®structure can be used mostly in the same way as DIBOND® in its standard version. Thus, it is well-suited for fabrication techniques such as sawing, cutting, milling, folding, 3-dimensionally formability, etc.

At a glance:

- Characteristic structure due to special coating system
- Special haptics and aesthetics
- Suitable for interior applications

DIBOND®structure is available in:  
Front: silver, Reverse: black

Width	1500		
Length	3050	4050	
Thickness	2	■	■
	3	■	■
	4	■	■

Dimensions are in mm



Sawing



Screwing



Guillotining




Drilling



Folding  
(V-groove)



Riveting



Routing



Clamp



3A Composites GmbH  
78224 Singen, Germany  
Tel +49 (0) 7731 80 29 89  
Fax +49 (0) 7731 80 21 05  
display.eu@3AComposites.com  
www.display.3AComposites.com